



**GUY ANCHOR
EXPANDING ROCK**

Originator: DSmith

Date: 7/7/06

Approval: DSmith

Date: 7/7/06

Page 1 of 1

Revision: J Mitchell

Date: 9/13/10

Stds Committee Approval:
Approved



Application: Used to guy utility poles in solid rock. A hole is drilled into the rock to a minimum 12 inch depth in line with the guy. The anchor is placed into the hole and a bar through the eye is used to turn and expand the anchor into the rock. The anchor expands and wedges against the wall of the rock.

Specification: List requirements as needed to describe the properties of the item. If necessary, use blanks () in description and add any of the following.

Dimensions:

Strength: Shall be capable of holding 23,000 pounds

Material: GALVANIZED Steel

Finish: The item shall be hot dipped galvanized

Packaging and Marking: Items shall be suitably packaged to prevent damage. The container shall be convenient for handling and storage. Manufacturer's name or symbol and catalog number shall be on each part or (and) its packaging.

Shipping: Special Shipping Instructions

Approved Manufacturers:

PUD IDENTIFICATION		MANUFACTURER CATALOG NUMBER	
Stock Description	Stock No.	HUBBELL	JOSLYN
ANCHOR, ROCK, 15"x3/4", TRIPLE EYE	005380	R315	J3436
ANCHOR, ROCK, 30"x3/4", TRIPLE EYE	005400	R330	J3437
ANCHOR, ROCK, 53"x3/4", TRIPLE EYE	005420	R353	J3438
ANCHOR, ROCK ,53"x 1", TRIPLE EYE	005460	R153L	JR153L
ANCHOR, ROCK ,72"x3/4", TRIPLE EYE	005440	R372	JR372
ANCHOR, ROCK ,72"x 1", TRIPLE EYE	005480	R172L	JR172L